

MATBP Series

Articulated Telescopic

Insulated Bucket Utility Vehicle

14 METERS
|—— TO —|
19 METERS

ANSI CATEGORY 'C' 46 kV and below

- Working height up to 19 Meters
- Side reach up to 14 Meters
- 200 kg to 275 kg platform capacity
- Mounted on 5-ton to 15-ton kg GVW chassis

STANDARD FEATURES

- ✓ Insulated, ANSI Category 'C' 46 kV and below
- ✓ Continuous rotation 360 degrees
- ✓ Minimum outreach 7 meters (200 kg)
- ✓ Lower boom/Chassis Insulation System
- ✓ Engine Start/Stop from control panel
- ✓ Energized line detector
- ✓ Overload alarm
- ✓ Outrigger Boom Interlock System with independent command For each outrigger
- ✓ Ground Egress
- ✓ Ideal for Live Line maintenance work
- ✓ Boom Tip Covers
- ✓ Safety Valves against any damage in hydraulic lines
- ✓ Actuated Warning Light System when boom is operational
- ✓ Articulation Foot Shoe for any type of land
- ✓ Safety at maximum load and lateral outreach
- ✓ Four Retractable Back Seats
- ✓ Tools & Equipment Cabinets

ADDITIONAL ACCESSORIES

- ☀️ HYDRAULIC CUTTER SAW
- ☀️ PORTABLE SEARCH LIGHT
- 🌊 HYDRAULIC PRESS
- 🔦 OUTRIGGER PADS
- 📡 WIRELESS INTERCOM (WALKIE TALKIE)
- 🚧 SAFETY CONES
- ☀️ ADJUSTABLE SEARCH LIGHTS FOR WORKING AT NIGHT

CHASSIS REQUIREMENTS

DRIVE TYPE	RIGHT HAND / LEFT HAND
GVWR 14.5 m - model	5-ton
GVWR 16 m - model	8-ton
GVWR 19 m - model	15-ton

GENERAL SPECIFICATIONS

WORKING HEIGHT
14 Meters - 19 Meters

SYSTEM PRESSURE
180* bar

PLATFORM CAPACITY
200 - 275 kgs

BURSTING STRENGTH
1400* bar

STOWED HEIGHT
3.3 meters

Boom Interlocking

*These values are approximate as per structure design



Contact

MERAJ Limited
Plot No 11, Sector 15,
Korangi Industrial Area,
Karachi-74900, Pakistan.

Tel: +9221-35050145/6
Fax: +9221-35060663
E-mail: sales@meraj.com

www.meraj.com

Text and photos are non-binding. The photos may show extra optionals only available at extra charge. The right to change make changes in accordance with technical progress is retained.



Special Application Trucks & Pumps | Since 1976